



Hardware Setup (EVS)



Step 1: Attach Camera

Remove Camera from Hardware Kit and attach to the quick release plate with the provided screw from the quick release assembly. Slide plate into the housing on top of the tripod.



Make Sure the
Lens Cover is
OPEN.



Step 2: Monitor

Remove the Monitor and Monitor Battery from the Hardware Kit. Attach the Monitor battery to the back side of the Monitor as shown to the right.



On the Tower, find the Monitor Attachment Plate. Insert the plate's mounting screw into the threaded receiver on the bottom of the monitor. Tighten securely.



Step 3: PowerPack battery

On the right side of the camera, remove the USB charging plug from its sheath on the camera hand strap.



Plug the USB Charging plug into the Sideline Power External PowerPack Battery and let it hang freely.



Step 4: Setting up Camera

Looking at the rear of the camera, locate the viewfinder camera screen on the left side of the camera. Flip the camera screen open to 90 degrees to power on the camera.



Open the the connections cover on the side of the camera body to reveal Micro HDMI port.



Step 5: Attaching Remote

Remove the Wired Remote and cable bundle from the hardware kit and attach the carabiner to the tension relief hook.



When connected, the carabiner should orient so the cord ends are pointing up toward the camera assembly.



Step 6: Connecting Remote to Camera

CAREFULLY plug in the Budget Remote's Multiport.



FRAGILE PLUG-IN On the right side of the camera toward the back, open the flap to expose the MultiPort plugin port. Plug the MultiPort cord into the MultiPort plugin port.



Step 7: Connecting HDMI Cable to Camera

CAREFULLY plug in HDMI cord with Micro HDMI adapter.



FRAGILE PLUG-IN Run HDMI cord through the camera's hand strap, and then up and over the camera. Then the Micro HDMI plug is inserted into the port we uncovered earlier on the LEFT SIDE of the camera.



Step 8: Connecting the Monitor

After the mast has been extended to the desired height, insert the HDMI plug into the monitor's 'HDMI IN' port



Press and release the on/off button to power on the monitor.



If desired, attach the Monitor Sun Visor.



Step 9: Using Remote

Test camera functionality with the remote and make sure camera zooms and records.



If you have any issues or questions, contact our service department at 800.496.4290 ext. 803.
Or email support@sidelinepower.com

