



Legacy MonoPod Setup Guide



MonoPod Hardware Kit Contents

Monitor Battery Charger

External Camera Battery

HDMI & MultiPort Cords

Camera Remote



Monitor Visor

Camera

Charging Cables

LCD Monitor

Monitor Battery

Step 1:

Remove MonoPod Tower from Travel Bag



Stand MonoPod vertically on ground.



Step 2:

Remove Camera from Hardware Kit and insert the MonoPod's base plate mounting screw into the threaded receiver on the bottom of the camera. Tighten securely.



Looking at the rear of the camera, locate the integrated camera screen on the left side of the camera. Flip the camera screen open to 90 degrees to power on the camera. Open the the connections cover on the side of the camera body to reveal Micro HDMI port.



2nd Picture Also shows a closer glimpse of how camera will attach to MonoPod

Step 3:

Attach HDMI & MultiPort Cords' Carabiner to Monopod's red tension relief harness



On the right side of the camera, remove the USB charging plug from its sheath on the camera retention strap.



Step 4:

CAREFULLY plug In MultiPort & Micro HDMI cords



FRAGILE PLUG-IN On the right side of the camera toward the back, open the flap to expose the MultiPort plugin port. The MultiPort cord, has yellow tag attached to it. Plug the MultiPort cord into the MultiPort plugin port.



FRAGILE PLUG-IN Take HDMI cord w/ Micro-HDMI converter and route it over the top of the camera for increased slack. The Micro HDMI plug is inserted into the port we uncovered earlier on the LEFT SIDE of the camera.

Step 5:

Plug the USB Charging plug into the Sideline Power External Battery and let it hang freely.



Step 6:

Remove the Monitor and Monitor Battery from the Hardware Kit. Attach the Monitor battery to the back side of the Monitor as shown to the right.



On the MonoPod Tower, find the Monitor Attachment Plate. Insert the plate's mounting screw into the threaded receiver on the bottom of the monitor. Tighten securely.

Monitor Attachment Plate

Monitor
Mounting
Screw



Step 7:

Locate the quick release levers for the mast locks. Starting with the top mast section, open the quick release lever and raise the mast section.

Recommended only raise top mast section half way.



Once a mast section is raised to the desired height, close the quick release lever, locking the mast lock and securing the mast section in place.



Continue this process until all mast sections have been extended and MonoPod is at desired height.

Step 8:

After the mast has been extended to the desired height, insert the HDMI plug into the monitor's 'HDMI IN' port



Step 9:

Press and release the on off button to power on the monitor. If desired, attach the Monitor Sun Visor.



Consider wrapping Camera Controller cord around monitor arm for location convenience



Step 10:

Test camera functionality with the remote and make sure everything is operating correctly.



If you have any issues or questions, contact our service department at 800.496.4290 ext. 803.
Or email support@sidelinepower.com

